Eaton EATS30N

Catalog Number: EATS30N

Eaton ATS rack PDU, 1U, Inputs Hardwired, 7.4 kW max, 30A, 200-240V, Output Hardwired

Photo is representative

Product Name	**Catalog Number**
Eaton ATS rack PDU	EATS30N
Product Length/Depth	**Product Height**
440 mm	43 mm
Product Width	**Product Weight**
390 mm	5 kg
Compliances	**Certifications**
CE Marked	CE

Powering Business Worldwide

□□

Mounting direction

Horizontal

Color

Black

Form factor

1U

Package contents

ATS
Quickstart guide
Safety instructions
Accessories for rack installation

Operating Temperature

0° to 40°C (32° to 104°F)

□□□□

Input connection

Hardwired

Wattage

7.4 kW max

Amperage Rating

30A

Input voltage

200-240V

Phase

Single-phase

Frequency rating

50/60 Hz

□□□□

Outlets

Hardwired

Outlet control

No

□□

Communication

HTTP, HTTPS, SSL, Telnet, FTP, SNMP, SMTP, DNS, DHCP, LDAP, RADIUS

SNMP

Yes

Ethernet interface

Yes

Serial interface

No

Mass configuration

Yes

□□□□

Electrical connection

Screwed terminal

Evaluation

At distance

Mounting Dimension (metrical)

43

Mounting dimension (standardized)

482.6 mm (19 inch)

Switchable

No

Over voltage category

2

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia